

Emblem Sign

RLM Reflectors

Job Information:

Project:

Prepared by:

Comments:

Approved by:

Features:

Reflector: Spun from heavy gauge aluminum with an rolled in bead.

Lamp Types:

Incandescent: 300W max. Medium base porcelain socket.

LED: Requires External Driver Enclosure.

LED(850/1250): Cree LMH2 Module with Osram Driver

LVE01: Cree CXA COB with Osram Driver, Requires Glass Jar

CFL: Requires External Driver Enclosure.

HPS: Requires External Driver Enclosure.

MH: 150W Max Requires External Driver Enclosure.

Mounting: Top Mounting with 3/4 NPT. For outdoor use, Teflon tape should be used around threads.

Finish: Powder Coat Finish for Outdoor use. Complete color selection found at bock.lighting/colors.

Certification: Built to UL 1598 and UL Certified for Damp and Wet Locations.



Size	Diameter	Height	Max Wattage
6208	8"	10-1/8"	100W
6210	10"	11-3/4"	150W
6212	12"	13-3/4"	200W
6214	14"	15-3/4"	300W
6218	18"	21-1/2"	300W
6222	22"	23-1/2"	300W

Note: This isn't a complete spec to order from. Bock offers more than what is shown on a single page. Use the RLM Catalog or RLM Configurator to make a valid part number and submittal.

<http://www.bocklighting.com/sales/rlm-configurator>

Ordering Guide:

Example: 6208-G0 / MED5 / 643-G0

Series	Lamp Type	Mounting
6208 = Emblem Sign 6210 = Emblem Sign 6212 = Emblem Sign 6214 = Emblem Sign 6218 = Emblem Sign 6222 = Emblem Sign	MED = Incandescent Base LED(850/1250) = LMH2 Module LVE01-(27/35/40K) @ (850/1250/1400/1800) = Cree CXA COB, Universal PSMH(50/70/100/150) = Pulse Start Metal Halide HPS(50/70/100/150) = High Pressure Sodium	Stem 640-(50/75) = Stem Mounting, 1/2" or 3/4" Cord 643 = Cord Mount, 10ft. Gooseneck GN23A GN24D